SECRET

P 070406Z FEB 68 1968 FEB 7 04 27 **Z** FM NPIC WASHDC TO RUCSAAA/SAC OFFUTT AFB OMAHA NEB OUT 64273 RUCVAAA/4080 STRAT WG OL 19 BARKSDALE AFB LA RUCVAAA/2D RTS BARKSDALE AFB LA RUEPJS/DIA WASHDC RUCIJRA/NAVRECONTECHSUPPCEN SUITLAND MD RUVBKNA/15TH AF MARCH AFB RIVERSIDE CALIF RUCVAAA/2 AF BARKSDALE AFB LA RUEFHQA/HQS USAF/AFRDR INFO RUEPIA/CIA WASHDC SECRET CITE NPIC 2929. 15TH AF (FOR DI). SAC (GLASS LAMP/DOCR, DM 4) 2D AF (FOR DI). AFRDR [25X1 FROM NATIONAL PHOTOGRAPHIC INTERPRETATION CENTER. 1. CAMERA B-18 WAS USED ON MISSION G-011 FLOWN 2 FEBRUARY 1968. PROCESSING WAS ACCOMPLISHED BY NAV. RECON. TECH. SUPPCEN. 2. ORIGINAL NEGATIVE: A. DENSITY IS GOOD THROUGHOUT THE MISSION. THERE IS A DISTINCT DIFFERENCE IN RESOLUTION BETWEEN THE IL'S AND IR'S, DISTRICTION 4 THE FORMER HAVING BETTER RESOLUTION OVER THE WHOLE FORMAT. Cy No. THE RESOLUTION RANGES FROM FAIR TO GOOD. B. 9R SIDE: A ROW OF MINUS DENSITY DOTS APPEARED IN ALL FORMATS 3.5 INCHES FROM THE OUTBOARD EDGE OF THE FORMAT AND 1.7 INCHES APART. FRAMES 761 AND 1369 CONTAIN MANUFACTURERS SPLICES; FRAME 881 CONTAINS A HEAT SPLICE. A 0.5 INCH WIDE PLUS DENSITY LINE RUNNING ACROSS THE FORMAT IS PRESENT IN FRAME 41. AN O.1 INCH WIDE AREA OF FOG EXTENDS ACROSS FRAME 1371 AT 75JG THE MIDDLE OF THE FRAME. THE 0.5 INCH MARGIN (OUTBOARD EDGE) OF FRAMES 1076 THROUGH 1079 ARE EXTENSIVELY FOGGED. C. 9L SIDE: MINUS DENSITY DOTS ARE PRESENT IN ALL FORMATS. ALTHOUGH THEY APPEAR TO BE RANDOM ACROSS THE FORMAT, THEY ARE TEC. EQUALLY SPACED ALONG THE MAJOR AXIS OF THE FILM. WAVERING PLUS DENSITY LINES ARE PRESENT INTERMITTENTLY THROUGHOUT THE MISSION. FRAME 002 CONTAINS A FOG STREAK EXTENDING 8.0 INCHES ACROSS 1.25 THE FORMAT (6.0 INCHES FROM THE DATA BLOCK END OF FORMAT). A 27.483-4 PLUS DENSITY STREAK IS PRESENT ACROSS FRAME 910 (2.5 INCHES FROM THE NON-DATA BLOCK END OF FORMAT). APPROXIMATELY THE LAST 25X1 489 FRAMES CONTAIN SEVERAL STRAIGHT PLUS DENSITY LINES ALONG THE MAJOR AXIS OF THE FILM. A MINOR EMULSION DEFECT IS PRESENT 4.0 INCHES FROM THE INBOARD EDGE AND 6.0 INCHES FROM THE DATA BLOCK END OF FRAME 1407. FRAMES 910 AND 911 CONTAIN HANDLING MARKS. Advance Copy FAINT IMAGES OF POSITION INDICATORS ARE PRESENT IN THE DATA BLOCK Sanitized IN ADDITION TO THE PROPERLY EXPOSED INDICATOR. FRAME 94 CONTAINS With Toxt A MANUFACTURERS SPLICE; FRAME 911 CONTAINS A HEAT SPLICE.

D. BOTH SIDES: FRAMES 509, 915, AND 1524 APPEAR SMEARED DUE TO VEHICLE MANEUVERING. A MINOR AREA OF FOG LOCATED NEAR THE VERTICAL INDICATOR DOT IS PRESENT IN ALL FORMATS. EDGE STATIC AND ROLLER CHATTER ARE PRESENT ALONG BOTH EDGES OF BOTH SIDES. FRAME 1682 IS A 3R. MODE 5 WAS USED THROUGHOUT. THE LAST TITLED FRAME IS 1684. THE COUNTER SKIPPED FRAME NUMBER 1682. 3. POSITIVES: A. PRINTING AND PROCESSING WERE GOOD. B. P.I. SUITABILITY IS FAIR TO GOOD DUE TO VARIABILITY IN RESOLUTION. C. CLOUDS OBSCURE APPROXIMATELY 30 PERCENT OF THE MISSION. GP-1 SECRET

SECRET

END OF MESSAGE